WP 2017 | Datasheet



WP410

Display:132*64 LCD 2 x Port 10/100 Audio HD wideband Presence PBX phonebooks 4 BLF keys (2 pages) PoE IEEE 802.3af Online call history Quick DND key VM notification Visual / audio BLF



All the features of WP410 +

2.8" color display 320*240 Coller image 2 x Gigabit Port 10/100/1000 Max 16 BLF keys (2 pages) 802.3az Green Ethernet Support of WPEHS



All the features of WP480G +

4.3" color display 480*272 Max 30 BLF keys (2 pages) + up to 3 extension modules Support of WP490EXT



Android 4.2 OS Touchscreen 7" color display 800*480 Caller image 2 x Port 10/100 Presence & Chat Audio HD wideband WiFi 802.11b/g/n Bluetooth 2.0 USB 2.0 PBX phonebooks Up to 120 BLF keys PoE IEEE 802.3af Online call history



All the features of WP600A +

7" color display 1024*600 2 x Gigabit Port 10/100/1000 Conference room phone: 2MP webcam

Support of WebRTC videoconference 802.3az Green Ethernet

Integration with doorphones: 2 way video + audio

Keypad Extension



Compatibility: WP490G 40 LED BLF keys (2 pages) 4.3" color display 272*480 Presence

Up to 3 modules in chain

Headsets



WHS-MONO - Monaural WHS-DUO - Binaural WHS-BT - Bluetooth

Wireless EHS Adapter



Compatibility: WP480G / WP490G

Compatible with Jabra, Plantronics and Sennheiser headsets *

Remote answer and hangup





www.wildix.com/voip-phones-and-headset/

WP4X0 / WP600AXX | Tech Specifications

WP410 / WP480G / WP490G	WP600A / WP600ACG	
Phone and PBX features		
	Android 4.2 OS; support for Android apps	
Presence	Presence and Chat	
	WP600ACG: WebRTC Kite videoconference	
New Voicemail notification	New Voicemail notification	
Online access to PBX phonebooks	Online access to PBX phonebooks	
Online call history	Online call history	
PBX ringtones	Selection and upload of ringtones	
Intercom, paging, speed dial, call on hold, 3-way conference, redial, mute, call transfer, call pickup, group call pickup, music on hold	Intercom, paging, speed dial, call on hold, 5-way conference, redial, mute, call transfer, call pickup, group call pickup, music on hold	
Multi-language support	Multi-language support	
Audio features		
HD Audio with wideband codec G.722	HD Audio with wideband codec G.722	
G.711a, G.711ulaw, G.729 codecs	G.711a, G.711ulaw, G.729 codecs	
Full-duplex speaker	Full-duplex speaker	
Echo canceller	Echo canceller	
Security		
SIP TLS	SIP TLS	
QoS VLAN	QoS VLAN	
RTP / RTCP	RTP / RTCP	
Physical features		
Volume, Redial, Transfer, Mute, Hold, Conference, Speaker, Headset, Phonebook, Voicemail hardware/software keys, 4 soft keys	Volume, Redial, Transfer, Mute, Hold, Conference, Speaker, Headset, Phonebook, Voicemail, Home, Menu hardware/software keys	
WP410: 4 BLF (2 pages); WP480G: 16 BLF (2 pages); WP490G: 30 BLF (2 pages)	Up to 120 BLF keys	
WP410: 2.3" display with backlight 132*64; WP480G: 2.8" color display with backlight 320*240; WP490G: 4.3" color display with backlight 480*272	WP600A: 7" color display, Capacitive Touch Screen, Resolution 800*480 WP600ACG: 7" color display, Capacitive Touch Screen, Resolution 1024*600	
1xRJ9 headset port, 1xRJ9 handset port, 1xEXT port (WP480G / WP490G)	1xRJ9 handset port; 1x3.5mm headset jack; 1xHDMl Video Out Port	
	Flash Memory 8GB, 1GB DDR3 Memory	
	Bluetooth 2.0; 1 USB 2.0; WiFi 802.11b/g/n;	
	WP600ACG: 2MP CMOS webcam with privacy shutter	
WP480G / WP490G: support of 802.3az (Energy-Efficient Ethernet)	WP600ACG: support of 802.3az (Energy-Efficient Ethernet)	
Wall-mountable: WP410; wall mount support for WP480G/WP490G (available on WMP)	Multi-position stand	
Power Adapter: Input: AC 100-240V; Output: DC 5V/1A	Power Adapter: Input: AC 100-240V; Output: DC 12V/1.2A	
Max power consumption: WP410: 1.3W; WP480G: 2.857W; WP490G: 5.51W; WP490 + 1 ext. module: 10,26W; WP490G + 2 ext. modules: 11.04W	Power consumption: ~ 6~10w	
PoE IEEE 802.3af WP410: PoE class 1; WP480G Class 2; WP490G: Class 0	PoE class 0, IEEE 802.3af	
WP410: 2 x RJ45 10/100 Mb Ethernet ports WP480G/WP490G: 2 x RJ45 10/100/1000 Mb Ethernet ports	WP600A: 2 x RJ45 10/100 Mb Ethernet ports WP600ACG: 2 x RJ45 10/100/1000 Mb Ethernet ports	
Optional external power supply (available on WMP)	Optional external power supply (available on WMP)	
WP410 Giftbox size: 207*197*102 mm, Weight: 0.8 kg WP480G Giftbox size: 274*258.5*142 mm, Weight: 1.6 kg WP490G Giftbox size: 285.5*224*96,2 mm, Weight:1.23 kg	Dimensions: 244*198*73mm, Weight: 1.04 kg	
Operating t°: 32~104 °F, 0~40 °C; Storage t°: 14~122 °F, -10 ~ 50 °C Humidity: 10 to 90 % Non-condensing	Operating t°: 32~104 °F, 0~40 °C; Storage t°: -4~158 °F, -20~70 °C Humidity: 10 to 90 % Non-condensing	



Accessories | Tech Specifications







Bluetooth

Monaural headset WHS-MONO	Binaural headset WHS-DUO	Monaural Bluetooth headset WHS-BT
Compatibility: WP4X0 / WP4X0G, WP600AV WP600ACG, W-AIR 70/100/150, WP 1st series	Compatibility: WP4X0 / WP4X0G, WP600A/ WP600ACG, W-AIR 70/100/150, WP 1st series	Compatibility: WP600A / WP600ACG, W-AIR 150
		Bluetooth 4.0
Noise canceling	Noise canceling	Noise canceling
Wideband Audio	Wideband Audio	Wideband Audio
Flex, 360° microphone	Flex, 360° microphone	Flex, 360° microphone
Ergonomic design, adjustable headband	Ergonomic design, adjustable headband	Ergonomic design, adjustable headband
Light weight	Light weight	Light weight
RJ9 cable for WP4X0/ WP4X0G new series, WP 1st series;	RJ9 cable for WP4X0 / WP4X0G new series, WP 1st series;	Compatible with iPhone, Android, Apple Mac and new generation Windows PC
3,5mm cable for WP600A / WP600ACG, W-AIR (compatible with iPhone and Android phones)	3,5mm cable for WP600A / WP600ACG, W-AIR (compatible with iPhone and Android phones)	
USB cord for call answer / hangup and volume control from Collaboration (Apple Mac and Windows PC)	USB cord for call answer / hangup and volume control from Collaboration (Apple Mac and Windows PC)	
		Talk time: 12 h; Standby time: 200 h
		Working range: up to 20 meters
		Charging time: 3 hours





Keypad expansion module WP490EXT

40 Programmable BLF Keys with LED (2 pages)

L4.3" color display, 272*480

Presence

2 x RJ12 (6P6C) Ports for data in and out

Power Adapter: Input: AC 100-240V; Output: DC 5V/1A

Powered by WP490(G) new series

Compatible with WP490(G) new series

Up to 3 Modules Daisy-chain



Wireless headset adapter WPEHS

Compatible wtih WP480G / WP490(G) new series

Compatible with Jabra, Plantronics and Sennheiser wireless headsets*:

* List of models:

Jabra: PRO 9450, GN 9350e, GN 9330e, GN 9125

Plantronics: Savi 700 Series (710, 720, 730, 740, 745), CS500 Series (510, 520, 530, 540), Voyager Legend CS

Sennheiser: DW Office (running firmware version 96 or later), SD Office

Answer and hangup calls remotely

Plug & Play

Powered by WP480G / WP490(G) new series

1 x RJ12 (6P6C) port for connection to WP480G / WP490(G) new series

1 x 3.5mm Jack for Plantronics headset

1 x RJ45 (8P8C) port for Jabra and Sennheiser headsets



